

## Tech Specs

UniFi UISP Branding

60 GHz Wireless Wireless Fiber Wired Accessory Tech

Wireless / airMAX Bullet AC IP67

Datasheet

Marketing Images



\*Compatible with airMAX devices.

### Mechanical

Dimensions	190 x 46 mm (7.72 x 1.81")
Weight	213 g (7.51 oz)
Enclosure materials	Aluminum, rubber
Weatherproofing	IP67

### Hardware

Networking interface	(1) GbE RJ45 port
Power method	24V assive PoE (pairs 4, 5+; 7, 8 return)
Power supply	24V DC, 0.3A (minimum)* * Not included with the BulletAC-IP67.
Max. power consumption	7W
Max. TX power	22 dBm
Throughput	
2.4 GHz	160+ Mbps
5 GHz	300+ Mbps
Antenna connector	N-type connector
ESD/EMP protection	Air/contact $\pm 24$ kV
LEDs	Power, Ethernet, (4) signal strength
Shock and vibration	ETSI300-019-1.4

Operating temperature	-40 to 70° C (-40 to 158° F)
Operating humidity	5 to 95% noncondensing
Certifications	CE, FCC, IC

---

### Operating Frequency (MHz)

US/CA	2400 - 2483.5 MHz
U-NII-1	5150 - 5250 MHz
U-NII-2A	5250 - 5350 MHz
U-NII-2C	5470 - 5725 MHz
U-NII-3	5725 - 5850 MHz
Worldwide	2400 - 2483.5 MHz 5150 - 5875 MHz

### Stay in Touch

 

[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2023 Ubiquiti, Inc. All rights reserved.