


Tech Specs

UniFi UISP Branding

60 GHz Wireless Wireless Fiber Wired Accessory Tech

Wireless / airMAX Lite AP

Datasheet Marketing Images



*Compatible with airMAX devices.

**24V DC, 0.5A GbE PoE adapter included.

Mechanical

Dimensions 452.3 × 78.7 × 54.4 mm (17.8 × 3.1 × 2.14")

Weight 420 g (14.82 oz)

Wind survivability 200 km/h (125 mph)

Wind loading 77 N at 200 km/h (17.3 lbf at 125 mph)

Hardware

Networking interface (1) GbE RJ45 port

Power method Passive PoE (pairs 4, 5+; 7, 8 return)

Power supply 24V, 0.5A Gigabit PoE adapter (Included)

Supported voltage range 20—26V DC

Antenna gain 16 dBi

ESD/EMP protectionAir/contact \pm 24kVShock and vibrationsETSI300-019-1.4

Operating temperature $-40 \text{ to } 70^{\circ} \text{ C } (-40 \text{ to } 158^{\circ} \text{ F})$

Operating humidity 5 to 95% noncondensing

Certifications CE, FCC, IC

Operating Frequency (MHz)

US/CA


 U-NII-1
 5150 - 5250 MHz

 U-NII-2A
 5250 - 5350 MHz

 U-NII-2C
 5470 - 5725 MHz

 U-NII-3
 5725 - 5850 MHz

 Worldwide
 5150 - 5875 MHz



© 2023 Ubiquiti, Inc. All rights reserved.