



- UniFi Cloud Gateways
- WiFi
- Switching
- Cloud Keys & Gateways
- Camera Security
- Door Access
- Phone System
- New Integrations
- Accessories

Switching / Flex Utility

Datasheet

Marketing Images

Mechanical

**Dimensions** Enclosure: 249 x 218 x 60 mm (9.8 x 8.6 x 2.4")  
 Adapter: 118.5 x 63 x 34.7 mm (4.7 x 2.5 x 1.4")

**Weight** Enclosure: 740 g (26.1 oz)  
 Adapter: 206 g (7.27 oz)

60W PoE Adapter

<b>Output voltage</b>	54V, 1.11A
<b>Rated voltage</b>	100-240V AC
<b>Input current</b>	Max. 1.5A
<b>Efficiency</b>	> 86%
<b>Output ripple</b>	200mVpp
<b>Line regulation</b>	< 1%
<b>Load regulation</b>	< 3%
<b>4-pair powering</b>	Pins 1, 2, 4, 5+ and Pins 3, 6, 7, 8-
<b>Operating temperature</b>	-20 to 60° C (-4 to 140° F)
<b>Storage temperature</b>	-30 to 70° C (-22 to 158° F)
<b>Operating humidity</b>	5 to 90%, noncondensing
<b>Surge immunity</b>	4kV difference and Common mode

Stay in Touch


