

Tech Specs

UniFi UIISP Branding

[UniFi Cloud Gateways](#)

[WiFi](#)

[Switching](#)

[Cloud Keys & Gateways](#)

[Camera Security](#)

[Door Access](#)

[Phone System](#)

[New Integrations](#)


[Accessories](#)

[Door Access](#) / G2 Starter Kit Professional

[Datasheet](#)

[Installation Guide](#)

[Marketing Images](#)



UA-Hub-Door Mechanical

Dimensions	174.9 x 126 x 32.9 mm (6.9 x 5 x 1.3")
Weight	363 g (12.8 oz)
Enclosure material	Polycarbonate
Mounting material	Polycarbonate

Hardware

Networking interface	(5) 10/100/1000 Base-T
Power method	PoE++ UL 294 Power-limited Class 2 PSU UL 60950/62368 LPS/PS2 PSU
Max. power consumption	Without PoE output: 30W With PoE output: 50W
PoE input	50V DC, 1A
PoE output	PoE passthrough, (4) PoE, 50V DC, total 20W
Button	(1) Factory-reset
LEDs	System: white/blue Output relays: white

Digital input	Request to exit/request to enter/remote release/door position sensor
Dry output relay	Lock: 30V DC, 1A Aux: 30V DC, 1A
Powered output relay	Lock: 12V DC, 1A Aux: 12V DC, 0.33A 12V DC, 0.33A
Operating environment	Indoor use only
Operating temperature	0 to 40° C (32 to 104° F)
Operating humidity	5 to 95% noncondensing
UL 294 level	Destructive attack: Level I Line security: Level I Endurance: Level I Standby power: Level I
UL 294 statement	Compliance with IEEE 802.3 (at or af) specifications was not verified as part of UL 294. The equipment is intended to comply with the section of the National Electrical Code, ANSI/NFPA 70, Article 725.121, Power Sources for Class 2 and Class 3 Circuits.
CAN/ULC-60839-11-1 Grade	Grade assignment: 1
Certifications	CE, FCC, IC, UL 294, CAN/ULC-60839-11-1
Document number, and issue date and/or revision level	UA-Hub-Door002, V01

Wiring Information

Typical installation (Shielded)	DC power input	Belden 8750 18 AWG 2 conductor (30.5 m/100 ft)
	Door position switch	Belden 8750 18 AWG 2 conductor (152.5 m/500 ft)
	Request to exit	Belden 8750 18 AWG 2 (152.5 m/500 ft)

Wiring gauge requirements (AWG)	Total length to device	Output load current at 12V DC			
		100mA	250mA	500mA	1A
				
	6.1 m (20 ft)	22	22	22	18
	15.2 m (50 ft)	22	22	22	18
30.5 m (100 ft)	22	22	18	18	

PoE cabling requirements The minimal conductor gauge permitted to connect between the PSE or power injector and the PD shall be 24 AWG (0.21 mm²) for horizontal or riser cable.

LEDs

PoE in	Steady blue: Adopted/device is ready Steady white: Pending adoption Blinking white/blue: Upgrading firmware
PoE out	Off: Not connected or no data link Steady blue: Connected and data link on

UA-G2-Pro Mechanical

Dimensions	160 x 40.4 x 40.55 mm (6.3 x 1.59 x 1.6")
Weight	136 g (4.8 oz)
Enclosure material	Polycarbonate, glass

Mount material	Aluminum alloy
Mounting	Wall, gang box
Weatherproofing	IP55

Hardware

Networking interface	(1) 10/100/1,000 MbE RJ45 port
Connectivity	BLE 4.2 NFC
Power method	PoE
Supported voltage range	48V DC
Max. power consumption	6W
ESD/EMP protection	Air: ±15kV, contact: ±8kV
Sensor	ToF sensor
Camera	4000 x 3000, 12 MP, 30 FPS
Microphone	Yes
Speaker	(1) 4 ohm, 1.5W
LEDs	R/G/B/W Flash
Button	(1) Factory-reset
NFC frequency	13.56 MHz
NFC read range	< 30 mm
NFC standards	ISO 14443A, 14443B, 15693
NFC technology	NFC Tag 1,2,3,4,5 MIFARE Classic MIFAREPlus MIFARE Ultralight MIFARE DESFire
Operating temperature	-10 to 45° C (14 to 113° F)
Operating humidity	5 to 90% noncondensing
Certifications	CE, FCC, IC

UA-G2

Mechanical

Dimensions	93 x 40 x 36.5 mm (3.7 x 1.6 x 1.4")
Weight	82 g (2.9 oz)
Enclosure material	Polycarbonate, glass
Mounting	In wall, gang box
Weatherproofing	IP55

Hardware

Networking interface	(1) 10/100 MbE RJ45 port
Connectivity	BLE 4.1
Power method	PoE
Supported voltage range	48V DC
Max. power consumption	5W

ESD/EMP protection	Air: ±15kV, contact: ±8kV
Sensors	Proximity sensor
Speaker	(1) 8 ohm, 0.7W
LEDs	R/G/B/W
Button	(1) Factory-reset
NFC frequency	13.56 MHz
NFC read range	< 30 mm
NFC standards	ISO 14443A, 14443B, 15693
NFC technology	NFC Tag 1,2,3,4,5 MIFARE Classic MIFAREPlus MIFARE Ultralight MIFARE DESFire
Operating temperature	-30 to 45° C (-22 to 113° F)
Operating humidity	5 to 90% noncondensing
Certifications	CE, FCC, IC

UA-Pocket Mechanical

Dimensions	84 x 39 x 7.4 mm (3.3 x 1.5 x 0.29")
Weight	16 g (0.56 oz)
Enclosure material	Polycarbonate, stainless steel
Weatherproofing	IP54

Hardware

NFC frequency	13.56 MHz
NFC technology	ISO/IEC 14443 Type A MIFARE DESFire EV3 4K UniFi Access Proprietary Security Protocol
Operating temperature	-10 to 45° C (14 to 113° F)
Operating humidity	10 to 90% noncondensing
Certification	CE

Stay in Touch

<input type="text" value="Email"/>	<input type="button" value="Subscribe"/>
------------------------------------	--

