

Tech Specs

UniFi UISP Branding

UniFi Cloud Gateways

WiFi

Switching

Cloud Keys & Gateways

Camera Security

Door Access

Phone System

New Integrations

Accessories

PoE Adapter

Datasheet

Marketing Images

Specifications

Model	U-POE-af
Dimensions	86 x 46 x 33 mm (3.39 x 1.81 x 1.30")
Weight	100 g (3,53 oz)
Output voltage	48V DC @ 0,32A
LAN activity indicator	No
Gigabit LAN port	Yes
Remote reset capability	No
Reset Button	No
Rated voltage	100—240V AC @ 50/60Hz
Input current	500mA Max.
Inrush current	<100A Peak at 25°C
Efficiency	84.25+%
Output ripple	200mV p-p
Switching frequency	65 kHz
Line regulation	≤ 3%
Load regulation	≤ 5%
2-pair powering	Pins 4, 5 (+) and 7, 8 (-)
4-pair powering	No
AC connector	IEC-320 C6
Data In / PoE	RJ45 shielded socket
Surge protection	Difference and common mode
Clamping protection	11V data, 60V power
Max. surge discharge	1500A (8/20 μ s) power
Peak pulse current	36A (10/1000 μ s) data
Shunt capacitance	<5 pF data
Response time	<1 ns
Operating temperature	0 to 40° C (32 to 104° F)
Storage temperature	-30 to 70°C (-22 to 158° F)
Operating humidity	10 to 95% noncondensing

Stay in Touch



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2023 Ubiquiti, Inc. All rights reserved.