



## MULTIHAUL™ TG TERMINAL UNIT T260

### Small Form Factor for Terragraph deployments

The MultiHaul™ TG system marks the release of Siklu's 3rd generation point to multipoint 60GHz products, this one with Terragraph certification. The TG network solution consists of Nodes operating over millimeter waves in a redundant mesh topology which also connect to Terminal Units (TU). The T260, Siklu's mini TG TU, communicates to the N36x TG Distribution node using the TG protocol, acting as an end point in a fully meshed MH TG topology. The T260 is Siklu's 3rd TG TU and incorporates several features from its predecessors. The T260 is a small and aesthetic Terminal Unit for the single-family home and other applications requiring gigabit performance in an easy to install form factor.

#### A Wide Range of Applications

- Fixed 5G Wireless Access, Gigabit to the Home, the MDU and the Enterprise
- Wi-Fi Hotspot Backhaul
- Security / Safe City Networks
- Smart City Business Services, Municipal networks

#### Small but Powerful

There can be no doubt that the smaller the TU is, the more options customers have for deployment. Typically, in wireless systems, going smaller means sacrificing performance. With the T260 Siklu has broken new ground delivering the full Gigabit in a form factor that is dramatically impressive with its smaller size.

#### Always-On Mission Critical Networks

When you can't afford to lose a video stream, critical safe city sensor data or any other mission critical data, you need a wireless network that's as reliable and secure as fiber. With maximal immunity to interference and hacker-proof links with embedded AES encryption, MultiHaul TG delivers a network you can count on. With the mesh topology there are built in redundant paths for traffic if an outage occurs in a given link.

#### Simple Integrated Future-safe Terminal Unit

Wireless infrastructure should be simple, and future proof. Organizations want to quickly deploy a single box across the target neighborhood, knowing that they have options to meet the interface requirements of any application. With a built-in software configured ethernet switch, the T260 Terminal Unit can address all your small form factor applications.

#### Fiber Quality with Wireless Flexibility

Siklu's millimeter wave radios successfully combine the capacity of fiber with the flexibility, speed of deployment and low TCO of wireless networks. That is what makes them the world's best-selling millimeter wave radios every year since 2011. They provide rock solid performance, even in very dense networks or under severe weather conditions, in thousands of networks around the globe.

#### Highly Secure and Physically Immune Beams

The narrow beamwidth confers several advantages including immunity to interference and network jamming. In contrast to wide-beam wireless systems that need to use multiple strategies to perform in dense areas. Multiple subscribers and services can be connected with complete isolation based on physical port, VLAN ID and/or a Terminal Unit.

#### Ready Set Go

The plug and play TU is designed for an easy single person installation. The patent-pending scanning antennas automatically aligns with serving Node(s). And with auto-connect no laptop or mobile device needed, the T260 allows plug and play deployment in a very short time.



## MULTIHAUL™ TG MINI TERMINAL UNIT T260

### 60GHz Terminal Unit Radio - specifications

The main specifications of the MultiHaul TG T260 are outlined in the following table.

<b>Topologies</b>	Point to Multi-point, L2 SDN Mesh
<b>Frequency &amp; Duplexing</b>	57-66GHz, TDD/TDMA, 4 channels.
<b>Channel Bandwidth, Modulation &amp; Adaptive Coding, TPC</b>	2160MHz, BPSK to QAM16, up to 10 levels of hitless adaptive bandwidth, coding, and modulation – boost gain by over 29dB. Automatic Transmit Power Control (ATPC), per link.
<b>Radio OTA Rate (over the air) / Throughput</b>	OTA up to 4,600Mbps / Throughput up to 1 Gbps symmetric.
<b>System Gain (link budget)</b>	110dB (Node to TU, including antenna gain). Please refer to Siklu SmartHaul™ Link Budget Calculator ( <a href="http://lbc.siklu.com">lbc.siklu.com</a> ) for radio link performance models.
<b>Self-alignment scanning, mechanical adjustment</b>	Horizontal scanning: 90°, Vertical scanning: ±12° / vertical elevation adjustment ±20°.
<b>Network synchronization</b>	To N36x nodes
<b>Interface (data + power)</b>	1x RJ-45 1GbE with PoE-In.
<b>Ethernet Features</b>	IEEE 802.1d transparent bridging, Provider bridge - VLAN & VLAN stacking.
<b>Security</b>	AES 128-bits OTA, GUI over HTTPS, CLI over SSH, IP-less operation.
<b>Management &amp; Provisioning</b>	In-band, Out-of-band management, Web GUI (one-pane configuration of local and remote units) & Embedded CLI, NETCONF, SNMP.
<b>Conformance</b>	Radio: US FCC 47 CFR Part 15.255; EN 303 722, EMC: US FCC 47 CFR Part 15; EN 301 489, Safety: UL/IEC 62368-1; UL/IEC 60950-22.
<b>Terragraph</b>	Terragraph certified.
<b>Power Supply</b>	PoE-In (IEEE 802.3af or passive), 11W.
<b>Environmental</b>	Operating Temperature: -4° ÷ +131°F (-20° ÷ +55°C); Ingress Protection Rating: IP67.
<b>Dimensions</b>	4.3 x 7.5 x 2.3 in. / 108 x 190 x 58 mm. (W x H x D), mounting kit not included.
<b>Weight</b>	3.9 lbs. / 1.8 Kg.
<b>In the Box</b>	Terminal unit with attached mounting kit, metallic bands, all weather shell, indoor PoE power supply with AC cable, grounding cable, quick start guide.