

## **Tech Specs**

UniFi UISP Branding

UniFi Cloud Gateways WiFi Switching Cloud Keys & Gateways Camera Security Door Access Phone System New Integrations Accessories

Camera Security / Al Theta Hub

Datasheet Installation Guide Marketing Images



## Mechanical

**Dimensions** 140 x 70 x 38 mm (5.5 x 2.8 x 1.5")

Weight UVC-AI-Theta-Hub: 330 g (11.6 oz)

UVC-AI-Theta-Hub Mount: 35 g (1.2 oz)

Enclosure material Aluminum alloy

Mount material Aluminum alloy

Video

Video compression H.264

Image settings Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay

System

Processor Quad-core Arm® Cortex®-A53 based chip

Networking interface GbE RJ45 port

Max. power consumption 12.5W

Power method PoE

**Supported voltage range** 37—57V DC

Output power 5V DC, 1A per port

**Display** 0.96" color display

**Button** Factory reset

Mounting Wall, ceiling mount

Operating temperature -20 to 40° C (-4 to 104° F)

Operating humidity 10 to 90% noncondensing

**Certifications** FCC, IC, CE

## Software

UniFi OS application UniFi Protect

**Mobile app** UniFi Protect iOS™ and Android™



© 2023 Ubiquiti, Inc. All rights reserved.